


Radio Transmission System Star Topology Node (FlexPower) DX80N2X2S-P1C



Type	DX80N2X2S-P1C
ID	3018796
Wireless data	
Type of radio	short-range
Installation	stationary
Topology	Star topology
Function	Star topology
Device type	Node
Frequency band	2.4-GHz ISM band
Frequency range	2.402 - 2.483 GHz
Number of radio channels	50
Channel width	1 MHz
Spread spectrum technology	FHSS (Frequency Hopping Spread Spectrum)
Single-Carrier Residence Time	7.8 ms
Response time typical	< 1000 ms
Output power ERP	18 dB/65 mW
Output power EIRP	20 dB/100 mW
I/O data	
Number of channels	2/4
Input type	NPN/0...20 mA or 0...10 V/thermistor
Number of channels	2
Output type	NMOS
Electrical data	
Runs with battery	Yes
Operating voltage U_s	3.6...5.5 VDC
Power-on indication	LED, Green
Mechanical data	
Design	Rectangular, DX80
Housing material	Plastic, PC
Antenna connection	RP-SMA female connector
Ambient temperature	-20...+80 °C
Protection class	IP20

- External antenna (RG58 RP-SMA connection)
- External terminal strip
- Integrated signal strength indicator
- Configuration via DIP switch
- Deterministic data transfer
- Frequency hopping FHSS
- Time Division Multiplex Access TDMA
- Transmission power: 63 mW, 18 dBm conducted, \leq 20 dBm EIRP
- External battery supply or 10...30VDC
- Inputs: 2 \times NPN, 2 \times 0...20 mA or 0...10V, 2 \times Thermistor
- Outputs: 2 \times NMOS

Functional principle

The DX80 system forms a radio-based network for wireless, bidirectional transmission of sensor signals in a star topology. It consists of a gateway that transmits the I/O signals to the control system and to as many as 47 nodes, with each node taking up to 12 sensors/actuators. The system is configured via the gateway with the included software. You can supply different components with DC voltage either via the power grid or self-sufficiently via battery or solar cell. Depending on the type of gateway used, simultaneous transmission of different measured and switching values is possible as well as communication via RS485 interface.

Norms:

FCC-ID UE300DX80-2400- This device complies with FCC para. 15, subpara. C, 15.247
ETSI/EN: In compliance with EN 300 328: V2.2.2 (2019-02)
IC: 7044A-DX8024

Tests/approvals		Radiation protection 10 V/m for 80–2700 MHz acc. to EN 61000-6-2
Approvals	ATEX II 3 G	
Approvals	CE	Shock and vibration resistance: IEC 68-2-6 and IEC 68-2-7
	CSA	
	ATEX	
Device marking	II 3 G Ex nA IIC T4 Gc	
Ex approval acc. to conformity certificate	LCIE 10 ATEX 1012 X	

Accessories

Type code	Ident no.		Dimension drawing
SMBDX80DIN	3077161	Mounting panel for DIN rail, suited for CP80, DX80, K80, Q80, operating temperature: -20...90 °C	

Function accessories

Type code	Ident no.		Dimension drawing
BWA-2O6-A	3081081	External antenna 6 dBi, N-female	
BWA-2O8-A	3081080	External antenna 8.5 dBi, N-female	
BWA-2O2-C	3077816	Internal antenna 2 dBi, RP-SMA male, standard	
BWA-2O5-C	3077817	Internal antenna 5 dBi, RP-SMA male	

Function accessories

Type code	Ident no.		Dimension drawing
BWA-207-C	3077818	Internal antenna 7 dBi, RP-SMA male	
DX81-LITH	3086016	Battery Case incl. XL-205F Battery	
DX81-LITH-NB	3086018	Battery case; Recommended Battery XL-205F	